
# Data Sheet - DFM 47GX900-MLP



## 47G Series

## DFM 47GX900-MLP

- IMX900 Pregius S Sensor
- 3.1 MP
- GigE Vision compliant
- Trigger and I/Os
- M12x0.5 Mount

The 47G series camera DFM 47GX900-MLP with a Sony IMX900 sensor delivers 36 frames per second with a resolution of 2048x1536 (3.1 MP).

47G Series: The Imaging Source's GigE board-level cameras feature a single-board design with an angled RJ45 connector, delivering an especially compact form factor, measuring just 36 x 36 x 18 mm. With robust data transmission and support for cable lengths up to 100 meters, the GigE board-level cameras ensure stable connectivity and flexible positioning in diverse environments. The cameras' modular design includes optional Power over Ethernet (PoE), as well as optional C mount, or M12 mount, enabling easy customization to meet various installation requirements and application needs.

The GigEVision standard allows for rapid integration into new and existing applications via The Imaging Source's IC Imaging Control 4 SDK as well as most other third-party image processing libraries.

Note: This Data Sheet is intended to provide a summary overview for an individual camera model.
The Imaging Source's website also offers information on spectral sensitivity, dimensional diagrams, sensor data sheets, STEP files as well as our full product catalog. For comprehensive technical information, please refer to the Technical Reference Manual specific to each camera model.
www.theimagingsource.com

# 1 Quick Facts

| General | |
|---|---|
| Vision Standard | GigE Vision |
| Resolution | 2048x1536 |
| Dynamic Range | 12 bit |
| Frame Rate at Full Resolution | 36 |

| Optical Interface | |
|---|---|
| IR-Cut filter | No |
| Sensor Type | Sony IMX900 |
| Shutter Type | Global |
| Sensor Format | 1/3.1 inch |
| Pixel Size | 2.25 µm |
| Lens Mount | M12x0.5 |


| Electrical Interface | |
|---|---|
| Interface | GigE |
| Supply Voltage | PoE: 48 VDC to 56 VDC |
| Power Consumption | approx 2.3 W PoE |


| Mechanical Data | |
|---|---|
| Dimensions | H: 36 mm, W: 38 mm, L: 18 mm |
| Mass | 20 g |


| Environmental Conditions | |
|---|---|
| Board Temperature (operating) | 0 °C to 70 °C |
| Temperature (storage) | -20 °C to 80 °C |
| Humidity (operating) | 20 % to 80 % (non-condensing) |
| Humidity (storage) | 20 % to 95 % (non-condensing) |


# 2 Dimensional Diagrams

## 2.1 DFM 47GX900-MLP Board Camera with PoE




Dimensions: mm
Tolerances: DIN ISO 2768-f

306-23-11-00-00

# 3 Spectral Characteristics

## 3.1 Spectral Sensitivity - IMX900

