

Ver.1.0

Diagonal 6.3 mm (Type 1 / 2.9) CMOS solid-state Image Sensor with Square Pixel for Color Cameras

Description

The IMX296LQR is a diagonal 6.3 mm (Type 1 / 2.9) CMOS active pixel type solid-state image sensor with a square pixel array and 1.58 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, digital 1.2 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and low PLS characteristics are achieved.
(Applications: Embedded Vision)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency
37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 1440 (H) × 1080 (V) approx. 1.55 M pixels
 - Readout mode
 - All-pixel scan mode
 - ROI mode
 - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in
 - All-pixel scan mode: 10 bit: 60.3 frame/s
- ◆ 10-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 24 dB: Analog Gain (0.1 dB step)
 - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
 - CSI-2 serial data output (1 Lane) RAW10 output
- ◆ Recommended lens F number: 2.8 or more (Close side)
- ◆ Recommended exit pupil distance: -100 mm to $-\infty$

Pregius

* Pregius is a registered trademark or trademark of Sony Group Corporation or its affiliates. The Pregius is global shutter pixel technology for active pixel-type CMOS image sensors that use Sony's low-noise CCD structure, and realizes high picture quality.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

◆ CMOS image sensor				
◆ Image size	Diagonal 6.3 mm (Type 1 / 2.9)	Approx. 1.58 M pixels	All-pixel	
◆ Total number of pixels	1456 (H) × 1098 (V)	Approx. 1.60 M pixels		
◆ Number of effective pixels	1456 (H) × 1088 (V)	Approx. 1.58 M pixels		
◆ Number of active pixels	1456 (H) × 1088 (V)	Approx. 1.58 M pixels		
◆ Number of recommended recording pixels	1440 (H) × 1080 (V)	Approx. 1.56 M pixels	All-pixel	
◆ Unit cell size	3.45 μm (H) × 3.45 μm (V)			
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel Vertical (V) direction: Front 10 pixels, rear 0 pixel			
◆ Package	138 pin LGA			

Image Sensor Characteristics

(T_j = 60 °C)

Item		Value	Remarks
Sensitivity (F5.6)	Typ.	1146 mV	1/30 s accumulation
Saturation signal	Min.	1001 mV	

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	1440 (H) × 1080 (V) approx. 1.56 M pixels	60.3	CSI-2	10

